

Angles:

Grades:

AISI 304/L (DIN 1.4301/7)
 AISI 316/L (DIN 1.4401/4)
 AISI 316Ti (DIN 1.4571)

Specifications:

Bended

DIN 1028 hot-rolled equal-leg angle


DIN 1029 hot-rolled unequal-leg angle

Certificate:

Upon request according EN 10204 3.1

Length:

Approximately length
 3-6 m.



Dimension (mm)	kg / m
20 x 20 x 3	0,88
25 x 25 x 3	1,12
25 x 25 x 4	1,45
30 x 30 x 3	1,36
30 x 30 x 4	1,78
30 x 30 x 5	2,18
35 x 35 x 4	2,10
40 x 40 x 3	1,813
40 x 40 x 4	2,42
40 x 40 x 5	2,97
50 x 50 x 3	2,284
50 x 50 x 4	3,014
50 x 50 x 5	3,77
50 x 50 x 6	4,47
60 x 60 x 5	4,57
60 x 60 x 6	5,42
70 x 70 x 7	7,38
80 x 80 x 8	9,66
90 x 90 x 9	12,2
100 x 100 x 10	15,0

Dimension (mm)	kg / m
20 x 10 x 3	0,66
25 x 15 x 3	0,88
30 x 15 x 3	1,056
30 x 20 x 3	1,12
30 x 20 x 4	1,45
40 x 20 x 3	1,36
40 x 20 x 4	1,76
45 x 30 x 5	2,673
50 x 30 x 4	2,42
50 x 30 x 5	2,97
60 x 30 x 5	3,564
60 x 40 x 5	3,78
60 x 40 x 6	4,47
80 x 40 x 5	4,57
80 x 40 x 6	5,42
80 x 40 x 8	7,23
100 x 50 x 6	6,78
100 x 50 x 8	9,04
100 x 50 x 10	11,2