

Angles:

Grades:

AISI 304/L (DIN 1.4301/7)

AISI 316/L (DIN 1.4401/4)

AISI 316Ti (DIN 1.4571)

Specifications:

Bended

DIN 1028 hot-rolled equal-leg angle


DIN 1029 hot-rolled unequal-leg angle

Certificate:

Upon request according EN 10204 3.1

Length:

Approximately length
3-6 m.



Dimension (mm)	kg / m	Dimension (mm)	kg / m
20 x 20 x 3	0,88	20 x 10 x 3	0,66
25 x 25 x 3	1,12	25 x 15 x 3	0,88
25 x 25 x 4	1,45	30 x 15 x 3	1,056
30 x 30 x 3	1,36	30 x 20 x 3	1,12
30 x 30 x 4	1,78	30 x 20 x 4	1,45
30 x 30 x 5	2,18	40 x 20 x 3	1,36
35 x 35 x 4	2,10	40 x 20 x 4	1,76
40 x 40 x 3	1,813	45 x 30 x 5	2,673
40 x 40 x 4	2,42	50 x 30 x 4	2,42
40 x 40 x 5	2,97	50 x 30 x 5	2,97
50 x 50 x 3	2,284	60 x 30 x 5	3,564
50 x 50 x 4	3,014	60 x 40 x 5	3,78
50 x 50 x 5	3,77	60 x 40 x 6	4,47
50 x 50 x 6	4,47	80 x 40 x 5	4,57
60 x 60 x 5	4,57	80 x 40 x 6	5,42
60 x 60 x 6	5,42	80 x 40 x 8	7,23
70 x 70 x 7	7,38	100 x 50 x 6	6,78
80 x 80 x 8	9,66	100 x 50 x 8	9,04
90 x 90 x 9	12,2	100 x 50 x 10	11,2
100 x 100 x 10	15,0		