

Grades:


AISI 304/L (DIN 1.4301/7)
 AISI 316/L (DIN 1.4401/4)
 AISI 316Ti (DIN 1.4571)

Details:

Cold drawn according to DIN 59051:
 approximate length 3–7 m
Hot rolled according to DIN 1024:
 approximate length 4–7 m

Certificate:

Upon request according EN 10204 3.1



B		H		S	kg/m
20	x	20	x	3	0,86
20	x	20	x	4	1,15
25	x	25	x	3	1,12
25	x	25	x	4	1,35
30	x	30	x	3	1,35
30	x	30	x	4	1,80
35	x	35	x	4	2,10
40	x	40	x	3	1,85
40	x	40	x	4	2,40
40	x	40	x	5	2,40
45	x	45	x	3	2,09
45	x	45	x	4	2,75
45	x	45	x	5	3,81
50	x	50	x	3	2,33
50	x	50	x	4	3,07
50	x	50	x	5	3,81

H		B		S	kg/m
50	x	50	x	6	4,57
60	x	30	x	5,5	3,70
60	x	40	x	4	3,2
60	x	60	x	4	3,7
60	x	60	x	5	4,6
60	x	60	x	6	5,5
70	x	35	x	6	4,7
70	x	70	x	7	6,3
80	x	40	x	7	6,2
80	x	80	x	6	7,3
80	x	80	x	8	9,7
90	x	90	x	9	12,2
100	x	50	x	8,5	9,0
100	x	100	x	10	15,1
120	x	60	x	10	12,8
120	x	120	x	13	25,1